



Write a program that controls a traffic light.

Objectives:

- Control the COLOR LED to simulate a traffic light using a single bulb
- Create a sequence of statements with proper timing controls

Your task is to write a program that controls a traffic light. The light will be simulated using the COLOR LED on the TI-Innovator™ Hub.

The COLOR LED should switch from green to yellow to red AND from red to green. Timing is up to you.

Your program will have a sequence of statements that simulate the change from RED to GREEN to YELLOW to RED. A sequence control structure in programming is a set of statements that are processed one after another, from top to bottom, without interruption.

Using Text as a Pause


The **Disp** command displays a message on the Home screen of the handheld. It can be used to display the value of a variable as in **Disp X**, or it can display a string. But it does not stop the program from continuing.

The **Text** statement on the **I/O** menu displays a dialog box and waits for the user to press enter or click the 'OK' button before processing the rest of the program. The effect of **Text** is shown to the right.



Setting up the Title Screen

1. Begin a new program, and call it `trafficlight`.
2. Select the **Text** keyword from the **I/O** menu.
3. In quotation marks, add the message *"Traffic Light: Press enter"* as shown.



Set the Colors

First, we set the color to red by sending the RGB values of 255 0 0.

In the example on the right, we use a **Wait** statement to tell the handheld to wait 5 seconds before sending the next command to the TI-Innovator Hub. The red light will stay on during this time.

Your task is to add the statements to make the light green, then yellow, and then red again.



Challenge: Add SOUNDS to indicate the color of the light.